NSN 5985-01-407-5508

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-407-5508

Application Design:
Transmission line
Body Material:
Metal Metal
Body Style:
Err-090
Overall Length:
1.850 inches
Overall Diameter:
Between 0.350 inches and 0.385 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.50 and 1.20 and 1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms: 50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average Rf Signal Attenuation In Decibels:
28.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz
Attenuation Accuracy Reference Frequency:
12.4 gigahertz
Attenuation Accuracy In Decibels:
-0.40/+0.40
Connection Type Per Function:
Female input and male output
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 12.400 gigahertz
Test Data Document:
81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-a-3933/14 government specification
Shelf Life:

N/a

NSN 5985-01-407-5508

Fixed Attenuator - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A20000