## NSN 5985-01-407-6677

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-407-6677

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.250 inches
Overall Height:
0.800 inches
Overall Width:
3.000 inches
Unthreaded Mounting Hole Diameter:
Between 0.110 inches and 0.130 inches
Distance Between Mounting Facility Centers:
2.720 inches
Voltage Standing Wave Ratio:
1.05
Coaxial Connector Series Designation:
Sma
Power Rating:
10.0 milliwatts average and 100.0 milliwatts peak
Attenuation Variation Method:
Stepped
Step Position Quantity:
60
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
4 unthreaded hole
Adjustment Device Type And Quantity:
1 electronic, programmable
Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female and 1 connector, receptacle
Specification Data:
94987-233809 manufacturers source control
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5985-01-407-6677

Variable Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A223a0