

View Online at <https://aerobasegroup.com/nsn/5985-01-407-8521>

Application Design:

Transmission line

Body Material:

Beryllium copper, qq-c-530

Body Style:

Err-090

Body Surface Treatment:

Any acceptable

Overall Length:

2.700 inches

Overall Diameter:

0.840 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Voltage Standing Wave Ratio:

1.25

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

N

Power Rating:

5.0 watts average and 1.0 kilowatts peak

Rf Signal Attenuation In Decibels:

40.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+12.4 gigahertz

Attenuation Accuracy In Decibels:

-0.80/+0.80

Connection Type Per Function:

Male input and female output

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 gigahertz and 12.400 gigahertz

Test Data Document:

81349-mil-a-3933/18 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-a-3933/18 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A20000