

View Online at <https://aerobasegroup.com/nsn/5985-01-408-8629>

Application Design:

Transmission line

Body Material:

Any acceptable

Body Style:

Rectangular terminal/terminals on three surfaces

Terminal Material:

Beryllium copper

Terminal Surface Treatment:

Gold plated, mil-g-45204

Body Surface Treatment:

Any acceptable

Overall Length:

0.765 inches

Overall Height:

0.160 inches

Overall Width:

0.250 inches

Mounting Hole/stud Quantity:

1

Unthreaded Mounting Hole Diameter:

Between 0.113 inches and 0.119 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Voltage Standing Wave Ratio:

1.15

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Power Rating:

30.0 watts peak

Rf Signal Attenuation In Decibels:

1.5

Voltage Standing Wave Ratio Frequency Range:

+0.960/+1.215 gigahertz

Attenuation Accuracy In Decibels:

-0.50/+0.50

Mounting Method:

Unthreaded hole

Terminal Type And Quantity:

2 tab, solder lug

Frequency Range:

Between 0.960 gigahertz and 1.215 gigahertz

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Specification Data:

13499-379-0569 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A20000