

View Online at <https://aerobasegroup.com/nsn/5985-01-408-8629>

**Application Design:**

Transmission line

**Body Material:**

Any acceptable

**Body Style:**

Rectangular terminal/terminals on three surfaces

**Terminal Material:**

Beryllium copper

**Terminal Surface Treatment:**

Gold plated, mil-g-45204

**Body Surface Treatment:**

Any acceptable

**Overall Length:**

0.765 inches

**Overall Height:**

0.160 inches

**Overall Width:**

0.250 inches

**Mounting Hole/stud Quantity:**

1

**Unthreaded Mounting Hole Diameter:**

Between 0.113 inches and 0.119 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.15

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Power Rating:**

30.0 watts peak

**Rf Signal Attenuation In Decibels:**

1.5

**Voltage Standing Wave Ratio Frequency Range:**

+0.960/+1.215 gigahertz

**Attenuation Accuracy In Decibels:**

-0.50/+0.50

**Mounting Method:**

Unthreaded hole

**Terminal Type And Quantity:**

2 tab, solder lug

**Frequency Range:**

Between 0.960 gigahertz and 1.215 gigahertz

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Specification Data:**

13499-379-0569 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A20000