## NSN 5985-01-408-9789

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-408-9789

| Application Design:                              |
|--|
| Transmission line                                |
| Body Material:                                   |
| Copper   |
| Body Style:                                      |
| Rectangular terminal/terminals on three surfaces |
| Overall Length:                                  |
| 0.650 inches                                     |
| Overall Height:                                  |
| 0.150 inches                                     |
| Overall Width:                                   |
| 0.375 inches                                     |
| Operating Tempurature Range:                     |
| -55.0/+125.0 degrees celsius                     |
| Voltage Standing Wave Ratio:                     |
| 1.30 and 1.50                                    |
| Input Impedance Rating In Ohms:                  |
| 50.0   |
| Output Impedance Rating In Ohms:                 |
| 50.0   |
| Power Rating:                                    |
| 0.5 watts average and 50.0 watts peak            |
| Rf Signal Attenuation In Decibels:               |
| 3.0  |
| Voltage Standing Wave Ratio Frequency Range:     |
| +0.0/+4.0 gigahertz and +4.0/+12.0 gigahertz     |
| Mounting Method:                                 |
| Terminal   |
| Terminal Type And Quantity:                      |
| 3 tab, solder lug                                |
| Frequency Range:                                 |
| Between 0.000 hertz and 12.000 gigahertz         |
| Specification Data:                              |
| 81413-202701 government specification            |
| Shelf Life:                                      |
| N/a  |
| Unit Of Measure:                                 |
|  |
| Demilitarization:                                |
| Yes - demil/mli                                  |
| Fiig:  |
| A20000   |