## NSN 5985-01-408-9802



Fixed Attenuator - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5985-01-408-9802	
Application Design:	
Transmission line	
Body Material:	
Any acceptable	
Body Style:	
Rectangular terminal/terminals on three surfaces	
Body Surface Treatment:	
Any acceptable	
Overall Length:	
Between 0.242 inches and 0.258 inches	
Overall Height:	
Between 0.757 inches and 0.773 inches	
Overall Width:	
Between 0.152 inches and 0.168 inches	
Mounting Hole/stud Quantity:	
1	
Unthreaded Mounting Hole Diameter:	
Between 0.113 inches and 0.119 inches	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Voltage Standing Wave Ratio:	
1.15	
Input Impedance Rating In Ohms:	
50.0	
Output Impedance Rating In Ohms:	
50.0	
Power Rating:	
30.0 watts average	
Rf Signal Attenuation In Decibels:	
1.0	
Attenuation Accuracy In Decibels:	
-0.125/+0.125	
Mounting Method:	
Unthreaded hole	

**Terminal Type And Quantity:** 

2 tab, solder lug

Frequency Range:

Between 960.000 megahertz and 1215.000 megahertz

**Precious Material And Location:** 

Terminals surfaces gold

**Precious Material:** 

Gold

## NSN 5985-01-408-9802

Fixed Attenuator - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000