NSN 5985-01-410-7652

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-410-7652

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches all flanges

Flange Inside Height:

0.503 inches all flanges

Flange Outside Width:

1.625 inches all flanges

Flange Outside Height:

1.625 inches all flanges

Flange Depth:

0.438 inches all flanges

Flange Connecting Hole Diameter:

0.046 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.11

Maximum Operating Pressure:

30.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Waveguide Longer Offset Distance:

2.000 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

Waveguide Offset Distance:

4.495 inches

Special Features:

200 kw peak and 200 w avg. Operting power

Flexibility:

Rigid all tubing segment

NSN 5985-01-410-7652

Waveguide Assembly - Page 2 of 2



| N/I | 9 | te | rı | 2 | |
|-----|---|----|----|---|--|
| | | | | | |

Aluminum alloy all tubing segment and flange

Style Designator:

Bend type

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A073a0