NSN 5985-01-411-5605

Waveguide Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-411-5605

Cross Sectional Shape:
Internal, rectangular external, rectangular
End Application:
Mc-130-e
Tubing Wall Construction Style:
Seamless single tubing segment
Flange Quantity:
2
Voltage Standing Wave Ratio:
1.10
Insertion Loss In Decibels:
0.06
Maximum Operating Pressure:
15.0 pounds per square inch gage
Waveguide Longer Offset Distance:
3.250 inches
Flange Connecting Facility And Quantity:
2 threaded hole all flanges all connection facilities
Flange Style:
Choke type all flanges
Waveguide Offset Distance:
2.000 inches
Specified Frequency:
Between 8.2 gigahertz and 12.4 gigahertz
Special Features:
3.5 inch bulkhead mtg. Flng
Flexibility:
Rigid single tubing segment
Material:
Aluminum alloy 6061 single tubing segment and flange
Surface Treatment:
Anodize single tubing segment and flange outside surfaces and paint single tubing segment and flange outside surfaces
Style Designator:
Bend type
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:

A073a0