## NSN 5985-01-412-4730

Fixed Attenuator - Page 1 of 2

**Application Design:** Transmission line



View Online at https://aerobasegroup.com/nsn/5985-01-412-4730

Body Material:
Aluminum alloy
Body Style:
Err-090
Terminal Material:
Steel, stainless
Terminal Surface Treatment:
Passivated
Overall Length:
Between 14.128 inches and 14.148 inches
Overall Diameter:
1.620 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N and sma
Power Rating:
200.0 watts average and 1.0 kilowatts peak
Rf Signal Attenuation In Decibels:
40.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+18.0 gigahertz
Attenuation Accuracy In Decibels:
-1.50/+1.50
Connection Type Per Function:
Male input and female output
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 gigahertz and 18.000 gigahertz
Specification Data:
30003-1209as736 manufacturers specification control

Shelf Life:

N/a

## NSN 5985-01-412-4730

Fixed Attenuator - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000