NSN 5985-01-413-9924

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-413-9924

Application Design:
Transmission line
Body Material:
Aluminum alloy and glass
Body Style:
Rectangular terminal/terminals on three surfaces
Overall Length:
Between 0.095 inches and 0.105 inches
Overall Height:
Between 0.005 inches and 0.015 inches
Overall Width:
Between 0.070 inches and 0.080 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
Power Rating: 100.0 milliwatts average
-
100.0 milliwatts average
100.0 milliwatts average Rf Signal Attenuation In Decibels:
100.0 milliwatts average Rf Signal Attenuation In Decibels: 13.0
100.0 milliwatts average Rf Signal Attenuation In Decibels: 13.0 Terminal Type And Quantity:
100.0 milliwatts average Rf Signal Attenuation In Decibels: 13.0 Terminal Type And Quantity: 4 tab, solder lug
100.0 milliwatts average Rf Signal Attenuation In Decibels: 13.0 Terminal Type And Quantity: 4 tab, solder lug Frequency Range:
100.0 milliwatts average Rf Signal Attenuation In Decibels: 13.0 Terminal Type And Quantity: 4 tab, solder lug Frequency Range: Between 0.000 hertz and 2.000 gigahertz
100.0 milliwatts average Rf Signal Attenuation In Decibels: 13.0 Terminal Type And Quantity: 4 tab, solder lug Frequency Range: Between 0.000 hertz and 2.000 gigahertz Specification Data:
100.0 milliwatts average Rf Signal Attenuation In Decibels: 13.0 Terminal Type And Quantity: 4 tab, solder lug Frequency Range: Between 0.000 hertz and 2.000 gigahertz Specification Data: 82577-6200191 manufacturers source control
100.0 milliwatts average Rf Signal Attenuation In Decibels: 13.0 Terminal Type And Quantity: 4 tab, solder lug Frequency Range: Between 0.000 hertz and 2.000 gigahertz Specification Data: 82577-6200191 manufacturers source control Shelf Life:
100.0 milliwatts average Rf Signal Attenuation In Decibels: 13.0 Terminal Type And Quantity: 4 tab, solder lug Frequency Range: Between 0.000 hertz and 2.000 gigahertz Specification Data: 82577-6200191 manufacturers source control Shelf Life: N/a
100.0 milliwatts average Rf Signal Attenuation In Decibels: 13.0 Terminal Type And Quantity: 4 tab, solder lug Frequency Range: Between 0.000 hertz and 2.000 gigahertz Specification Data: 82577-6200191 manufacturers source control Shelf Life: N/a
100.0 milliwatts average Rf Signal Attenuation In Decibels: 13.0 Terminal Type And Quantity: 4 tab, solder lug Frequency Range: Between 0.000 hertz and 2.000 gigahertz Specification Data: 82577-6200191 manufacturers source control Shelf Life: N/a Unit Of Measure:
100.0 milliwatts average Rf Signal Attenuation In Decibels: 13.0 Terminal Type And Quantity: 4 tab, solder lug Frequency Range: Between 0.000 hertz and 2.000 gigahertz Specification Data: 82577-6200191 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization:
100.0 milliwatts average Rf Signal Attenuation In Decibels: 13.0 Terminal Type And Quantity: 4 tab, solder lug Frequency Range: Between 0.000 hertz and 2.000 gigahertz Specification Data: 82577-6200191 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli