NSN 5985-01-414-6410



View Online at https://aerobasegroup.com/nsn/5985-01-414-6410

Fixed Attenuator - Page 1 of 2 **Application Design:** Transmission line **Body Material:** Copper alloy and glass, metallized and copper **Body Style:** Rectangular terminal/terminals on three surfaces **Terminal Surface Treatment:** Gold plated, mil-g-45204 **Overall Length:** 0.750 inches **Overall Height:** 0.150 inches **Overall Width:** 0.515 inches Mounting Hole/stud Quantity: 1 **Unthreaded Mounting Hole Diameter:** 0.116 inches **Operating Tempurature Range:** -55.0/+150.0 degrees celsius Voltage Standing Wave Ratio: 1.15 and 1.35 and 1.50 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Rf Signal Attenuation In Decibels:** 20.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+1.0 gigahertz and +1.0/+2.5 gigahertz and +2.5/+4.0 gigahertz **Mounting Method:** Unthreaded hole **Terminal Type And Quantity:** 2 tab, solder lug **Frequency Range:** Between 0.000 hertz and 4.000 gigahertz **Precious Material And Location:** Terminal surfaces gold **Precious Material:**

Gold

Shelf Life:

N/a

NSN 5985-01-414-6410

Fixed Attenuator - Page 2 of 2

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A20000

