

View Online at <https://aerobasegroup.com/nsn/5985-01-414-6410>

Application Design:

Transmission line

Body Material:

Copper alloy and glass, metallized and copper

Body Style:

Rectangular terminal/terminals on three surfaces

Terminal Surface Treatment:

Gold plated, mil-g-45204

Overall Length:

0.750 inches

Overall Height:

0.150 inches

Overall Width:

0.515 inches

Mounting Hole/stud Quantity:

1

Unthreaded Mounting Hole Diameter:

0.116 inches

Operating Temperature Range:

-55.0/+150.0 degrees celsius

Voltage Standing Wave Ratio:

1.15 and 1.35 and 1.50

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Rf Signal Attenuation In Decibels:

20.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+1.0 gigahertz and +1.0/+2.5 gigahertz and +2.5/+4.0 gigahertz

Mounting Method:

Unthreaded hole

Terminal Type And Quantity:

2 tab, solder lug

Frequency Range:

Between 0.000 hertz and 4.000 gigahertz

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A20000