## NSN 5985-01-414-8642

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-414-8642

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.750 inches
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Voltage Standing Wave Ratio:
1.20 and 1.35
Coaxial Connector Series Designation:
Sma
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0 to 127.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
128
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
5 threaded hole
Frequency Range:
Between 0.000 hertz and 1.500 gigahertz
Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:
1 electronic, programmable
Mounting Facility Screw Thread Diameter:
0.112 inches
Immedence Deting In Ohmer
Impedance Rating In Ohms:
50.0 input-output
50.0 input-output
50.0 input-output Terminal Type And Quantity:
<ul> <li>50.0 input-output</li> <li>Terminal Type And Quantity:</li> <li>2 connector, coaxial, female and 9 pin</li> </ul>

---

## NSN 5985-01-414-8642

Variable Attenuator - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A223a0

