NSN 5985-01-415-1465

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-415-1465

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.260 inches
Overall Height:
2.000 inches
Overall Width:
0.500 inches
Unthreaded Mounting Hole Diameter:
0.130 inches
Distance Between Mounting Facility Centers:
2.350 inches
Voltage Standing Wave Ratio:
2.00
Coaxial Connector Series Designation:
Sma
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.4
Overall Attenuation Range In Decibels:
+0.0/+60.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
2 unthreaded hole
Frequency Range:
Between 0.750 gigahertz and 2.250 gigahertz
Adjustment Device Type And Quantity:
1 electronic, voltage controlled
Mounting Facility Pattern:
Two position in-line
Mounting Facility Screw Thread Diameter:
0.130 inches
Impedance Rating In Ohms:
10000.0 input
Terminal Type And Quantity:
2 connector, coaxial, female and 4 pin
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5985-01-415-1465

Variable Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A223a0