

View Online at <https://aerobasegroup.com/nsn/5985-01-417-0069>

Frequency Rating:

8.0 gigahertz 4th frequency crosstalk reference and 12.4 gigahertz 4th frequency crosstalk reference

Unthreaded Mounting Hole Diameter:

0.104 inches

Switch Type:

Nontransfer

Operating Temperature Range:

-65.0/+110.0 degrees celsius

Voltage Standing Wave Ratio:

1.75 3rd

Insertion Loss In Decibels:

3.50 5th

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female and male

Rf Power Handling Capability:

0.5 watts average single

Minimum Crosstalk Rating In Decibels:

70.0 5th

Actuator Current Type And Rating In Amps:

0.075 dc

Actuator Voltage In Volts:

12.0

Switching Time:

10.0 nanoseconds

Pole Quantity:

1

Throw Quantity:

1

Coupling Position Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Material:

Metal body

Terminal Type And Quantity:

2 pin and 3 receptacle, coaxial and 1 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A158a0