

View Online at <https://aerobasegroup.com/nsn/5985-01-417-0074>

**Frequency Rating:**

4.0 gigahertz 2nd frequency insertion loss reference and 8.0 gigahertz 2nd frequency insertion loss reference

**Unthreaded Mounting Hole Diameter:**

0.104 inches

**Switch Type:**

Nontransfer

**Distance Between Mounting Facility Centers:**

1.000 inches single mounting facility pattern

**Voltage Standing Wave Ratio:**

1.80 2nd

**Insertion Loss In Decibels:**

3.60 4th

**Coaxial Connector Series Designation:**

Sma

**Connector End Design:**

Female

**Minimum Crosstalk Rating In Decibels:**

65.0 2nd

**Actuator Operating Method:**

Solid state

**Switching Time:**

50.0 nanoseconds

**Pole Quantity:**

1

**Throw Quantity:**

5

**Coupling Position Quantity:**

5

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Mounting Facility Pattern:**

Two position in-line single mounting facility pattern

**Material:**

Metal body

**Terminal Type And Quantity:**

2 pin and 6 receptacle, coaxial

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A158a0