

View Online at <https://aerobasegroup.com/nsn/5985-01-417-2057>

**Frequency Rating:**

10.0 megahertz single frequency operating and 2.0 gigahertz single frequency operating

**Unthreaded Mounting Hole Diameter:**

0.150 inches

**Switch Type:**

Nontransfer

**Intermediate Horizontal Distance Between Mounting Centers:**

2.415 inches single mounting facility pattern

**Voltage Standing Wave Ratio:**

2.00 single

**Insertion Loss In Decibels:**

3.50 single

**Coaxial Connector Series Designation:**

Smc and sma

**Minimum Crosstalk Rating In Decibels:**

45.0 single

**Actuator Operating Method:**

Solid state

**Switching Time:**

65.0 nanoseconds

**Pole Quantity:**

1

**Throw Quantity:**

5

**Coupling Position Quantity:**

5

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Mounting Facility Pattern:**

Four position rectangular single mounting facility pattern

**Material:**

Metal body

**Terminal Type And Quantity:**

1 connector, receptacle and 6 receptacle, coaxial

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A158a0