NSN 5985-01-418-6123

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-418-6123

Application Design:
Transmission line
Body Style:
Irregular
Overall Length:
3.000 inches
Overall Height:
0.800 inches
Overall Width:
1.300 inches
Voltage Standing Wave Ratio:
1.25
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average and 10.0 watts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
3.0
Overall Attenuation Range In Decibels:
+0.0/+24.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
6
Attenuation Per Step In Decibels:
1.0 and 2.0 and 4.0 and 8.0 and 16.0 and 24.0
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 10.000 megahertz and 1.200 gigahertz
Mounting Thread Quantity:
40 per inch
Mounting Facility Pattern:
Four position rectangular
Terminal Type And Quantity:
2 connector, coaxial, female and 7 solder stud
Shelf Life:
N/a
Unit Of Measure:
Unit Of Measure:

--

NSN 5985-01-418-6123

Variable Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A223a0