# NSN 5985-01-418-6124

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-418-6124

# Application Design:

Transmission line

#### **Body Style:**

Irregular

## Overall Length:

4.000 inches

#### **Overall Height:**

0.800 inches

#### **Overall Width:**

1.380 inches

#### Voltage Standing Wave Ratio:

1.25

## **Coaxial Connector Series Designation:**

Sma

#### **Power Rating:**

1.0 watts average and 50.0 watts peak

## Mounting Facility Screw Thread Series Designator:

Unc

#### Insertion Loss At Minimum Attenuation In Maximum Decibels:

3.8

## **Overall Attenuation Range In Decibels:**

+0.0/+24.0

## **Attenuation Variation Method:**

Continuous

## Mounting Facility Type And Quantity:

4 threaded hole

## Frequency Range:

Between 900.000 megahertz and 1.200 gigahertz

## Mounting Facility Pattern:

Four position rectangular

## Mounting Facility Screw Thread Diameter:

0.112 inches

## Mounting Thread Tolerance Class:

2b internal

## **Terminal Type And Quantity:**

2 connector, coaxial, female and 9 solder stud

#### Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

# NSN 5985-01-418-6124

Variable Attenuator - Page 2 of 2

**Fiig:** A223a0

