NSN 5985-01-418-6124

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-418-6124 **Application Design:** Transmission line **Body Style:** Irregular **Overall Length:** 4.000 inches **Overall Height:** 0.800 inches **Overall Width:** 1.380 inches **Voltage Standing Wave Ratio:** 1.25 **Coaxial Connector Series Designation:** Sma **Power Rating:** 1.0 watts average and 50.0 watts peak **Mounting Facility Screw Thread Series Designator:** Unc **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 3.8 **Overall Attenuation Range In Decibels:** +0.0/+24.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 4 threaded hole Frequency Range: Between 900.000 megahertz and 1.200 gigahertz **Mounting Facility Pattern:** Four position rectangular **Mounting Facility Screw Thread Diameter:** 0.112 inches **Mounting Thread Tolerance Class:** 2b internal **Terminal Type And Quantity:** 2 connector, coaxial, female and 9 solder stud Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5985-01-418-6124

Variable Attenuator - Page 2 of 2



Fiig:

A223a0