

View Online at <https://aerobasegroup.com/nsn/5985-01-419-1916>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b second flange single connection facility

**Thread Direction:**

Right-hand second flange single connection facility

**Tubing Wall Construction Style:**

Seamless second tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.005 inches first flange

**Flange Inside Height:**

0.505 inches first flange

**Flange Outside Width:**

1.625 inches second flange

**Flange Outside Height:**

1.625 inches first flange

**Flange Inside Diameter:**

1.220 inches first flange

**Flange Depth:**

0.438 inches second flange

**Flange Connecting Hole Diameter:**

0.169 inches first flange single connection facility

**Voltage Standing Wave Ratio:**

1.08

**Waveguide Outside Width:**

1.000 inches

**Thread Size:**

0.164 inches second flange single connection facility

**Waveguide Inside Width:**

0.900 inches

**Waveguide Inside Height:**

0.400 inches

**Waveguide Outside Height:**

0.500 inches

**Waveguide Longer Offset Distance:**

12.870 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole first flange single connection facility

**Flange Style:**

Cover type first flange

**Waveguide Offset Distance:**

3.220 inches

**Flexibility:**

Rigid second tubing segment

**Material:**

Copper alloy first tubing segment and flange

**Precious Material And Location:**

Waveguide and flange surfaces silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver first tubing segment and flange all surfaces and rubber first tubing segment and flange all surfaces

**Style Designator:**

Bend type

**Thread Series Designator:**

Unc second flange single connection facility

**Specification Data:**

92685-9900c01599 manufacturers source control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0