NSN 5985-01-420-2655

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-420-2655

C	Castia	nal Shape:	
CIOSS	Section	nai Snabe:	

Internal, rectangular external, rectangular

Thread Class:

2b second flange single connection facility

Thread Direction:

Right-hand second flange single connection facility

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.362 inches first flange

Flange Inside Height:

0.222 inches first flange

Flange Outside Width:

0.750 inches second flange

Flange Outside Height:

0.750 inches second flange

Flange Inside Diameter:

0.596 inches second flange

Flange Depth:

0.285 inches second flange

Flange Connecting Hole Diameter:

0.116 inches first flange single connection facility and 0.118 inches first flange single connection facility

Waveguide Outside Width:

0.360 inches

Thread Size:

0.112 inches second flange single connection facility

Waveguide Inside Width:

0.280 inches

Waveguide Inside Height:

0.140 inches

Waveguide Outside Height:

0.220 inches

Waveguide Longer Offset Distance:

4.634 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange single connection facility

Flange Style:

Cover type first flange

Waveguide Offset Distance:

1.110 inches

NSN 5985-01-420-2655

Waveguide Assembly - Page 2 of 2



Flexibility:
Rigid single tubing segment
Material:
Aluminum alloy 6061 single tubing segment and flange
Style Designator:
Bend type
Thread Series Designator:
Unc second flange single connection facility
Specification Data:
20418-873952 manufacturers specification control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A073a0