## NSN 5985-01-422-1066



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-422-1066 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** Err-090 **Body Surface Treatment:** Passivated **Overall Length:** 1.200 inches **Overall Diameter:** 0.360 inches **End Application:** Dmt-37a **Voltage Standing Wave Ratio:** Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Wpm **Power Rating:** 2.0 watts average and 5000.0 watts peak **Rf Signal Attenuation In Decibels:** 10.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz **Attenuation Accuracy In Decibels:** -0.30/+0.30 **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 gigahertz and 12.000 gigahertz **Special Features:** Given frequency range is for the 1.15 swr but the freq range is 0 to 12.0 ghz and insertion loss and attenuation is calibrated at dc, 4.0, 8.0 and 12.0 ghz.

--

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5985-01-422-1066

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000