## NSN 5985-01-428-3614

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-428-3614

Application Design:
Waveguide
Body Style:
Coaxial type
Overall Length:
3.150 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.750 inches
Overall Height:
1.610 inches
Overall Width:
1.280 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.750 inches
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+60.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 0.000 megahertz and 2000.000 megahertz
Overall Attenuation Accuracy In Decibels:
-0.50/+0.50
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
Adjustinont before Type And Quantity.

1 shaft

## NSN 5985-01-428-3614

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern:
Four position diamond
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.138 inches
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A223a0