NSN 5985-01-433-0378



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-433-0378 **Application Design:** Transmission line **Body Style:** Irregular **Overall Length:** 3.000 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.720 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.400 inches **Overall Height:** Between 0.790 inches and 0.850 inches **Overall Width:** 2.000 inches **Unthreaded Mounting Hole Diameter:** 0.125 inches **Voltage Standing Wave Ratio:** 1.80 **Coaxial Connector Series Designation:** Sma **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 2.7 **Overall Attenuation Range In Decibels:** +0.0/+64.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 4 unthreaded hole Frequency Range: Between 6.000 gigahertz and 12.000 gigahertz **Adjustment Device Type And Quantity:** 1 electronic, programmable **Mounting Facility Pattern:** Four position rectangular **Terminal Type And Quantity:** 3 connector, coaxial, female and 1 connector, receptacle Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5985-01-433-0378

Variable Attenuator - Page 2 of 2



Fiig:

A223a0