

View Online at <https://aerobasegroup.com/nsn/5985-01-433-0379>

**Application Design:**

Transmission line

**Body Style:**

Irregular

**Overall Length:**

1.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.235 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.500 inches

**Overall Height:**

0.220 inches

**Overall Width:**

0.860 inches

**Unthreaded Mounting Hole Diameter:**

0.093 inches

**Voltage Standing Wave Ratio:**

1.50

**Coaxial Connector Series Designation:**

Sma

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

2.5

**Overall Attenuation Range In Decibels:**

+0.0/+31.0

**Attenuation Variation Method:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Frequency Range:**

Between 0.000 hertz and 2.000 gigahertz

**Overall Attenuation Accuracy In Decibels:**

-0.20/+0.20

**Adjustment Device Type And Quantity:**

1 electronic, programmable

**Mounting Facility Pattern:**

Four position rectangular

**Impedance Rating In Ohms:**

50.0 input-output

**Terminal Type And Quantity:**

2 connector, coaxial, female and 11 pin

**Specification Data:**

55827-g1-22-9040 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A223a0