

View Online at <https://aerobasegroup.com/nsn/5985-01-433-0379>

Application Design:

Transmission line

Body Style:

Irregular

Overall Length:

1.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.235 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches

Overall Height:

0.220 inches

Overall Width:

0.860 inches

Unthreaded Mounting Hole Diameter:

0.093 inches

Voltage Standing Wave Ratio:

1.50

Coaxial Connector Series Designation:

Sma

Insertion Loss At Minimum Attenuation In Maximum Decibels:

2.5

Overall Attenuation Range In Decibels:

+0.0/+31.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole

Frequency Range:

Between 0.000 hertz and 2.000 gigahertz

Overall Attenuation Accuracy In Decibels:

-0.20/+0.20

Adjustment Device Type And Quantity:

1 electronic, programmable

Mounting Facility Pattern:

Four position rectangular

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female and 11 pin

Specification Data:

55827-g1-22-9040 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0