## NSN 5985-01-433-2833

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-433-2833
Application Design:
Transmission line
Body Material:
Brass
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
1.030 inches
Overall Diameter:
0.317 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.15
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Bnc
Power Rating:
2.0 watts average and 500.0 watts peak
Rf Signal Attenuation In Decibels:
30.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Test Data Document:
81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

## NSN 5985-01-433-2833

Fixed Attenuator - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000

Mil-std (military Standard):

Mil-a-3933 spec.