

View Online at <https://aerobasegroup.com/nsn/5985-01-433-3259>

Body Style:

Rectangular

Overall Length:

2.232 inches

Overall Height:

1.340 inches

Overall Width:

0.500 inches

Frequency Rating:

0.0 gigahertz single frequency voltage standing wave ratio and 18.0 gigahertz single frequency voltage standing wave ratio

Unthreaded Mounting Hole Diameter:

0.094 inches

Switch Type:

Nontransfer

Distance Between Mounting Facility Centers:

1.188 inches single mounting facility pattern

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.50 single

Insertion Loss In Decibels:

0.50 single

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Rf Power Handling Capability:

25.0 watts average single

Minimum Crosstalk Rating In Decibels:

60.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.14 dc

Actuator Voltage In Volts:

28.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

20.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

2 unthreaded hole

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Material:

Copper cover

Unpackaged Unit Weight:

60.0 grams

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Surface Treatment:

Nickel cover all surfaces

Terminal Type And Quantity:

3 receptacle, coaxial and 2 tab, solder lug

Specification Data:

26512-gs839jh manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0