## NSN 5985-01-433-4736

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-433-4736

## Application Design:

Transmission line

#### **Body Material:**

Steel, corrosion resisting

## Body Style:

Err-090

#### **Terminal Material:**

Steel, corrosion resisting

#### **Terminal Surface Treatment:**

Passivated

#### **Body Surface Treatment:**

Passivated

#### **Overall Length:**

Between 0.840 inches and 0.880 inches

#### **Overall Diameter:**

0.400 inches

#### **Operating Tempurature Range:**

-55.0/+100.0 degrees celsius

#### Voltage Standing Wave Ratio:

1.25

#### Input Impedance Rating In Ohms:

50.0

#### **Output Impedance Rating In Ohms:**

50.0

#### **Coaxial Connector Series Designation:**

Sma

#### **Power Rating:**

2.0 watts average and 0.2 kilowatts peak

### **Rf Signal Attenuation In Decibels:**

5.0

### Voltage Standing Wave Ratio Frequency Range:

+8.0/+12.4 gigahertz

#### Attenuation Accuracy In Decibels:

-0.30/+0.30

#### **Connection Type Per Function:**

Female input and male output

#### **Mounting Method:**

Connector

#### **Terminal Type And Quantity:**

2 connector

#### **Frequency Range:**

Between 8.000 gigahertz and 12.400 gigahertz

# NSN 5985-01-433-4736

Fixed Attenuator - Page 2 of 2



**Specification Data:** 

82577-h970065 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A20000