

View Online at <https://aerobasegroup.com/nsn/5985-01-433-7247>

Body Style:

Rectangular

Overall Length:

2.560 inches

Overall Height:

2.180 inches

Overall Width:

1.322 inches

Frequency Rating:

0.0 gigahertz single frequency voltage standing wave ratio and 3.0 gigahertz single frequency voltage standing wave ratio

Unthreaded Mounting Hole Diameter:

0.149 inches

Switch Type:

Nontransfer

Longest Horizontal Distance Between Mounting Centers:

0.800 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

1.800 inches single mounting facility pattern

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.20 single

Insertion Loss In Decibels:

0.20 single

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Minimum Crosstalk Rating In Decibels:

80.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.28 dc

Actuator Voltage In Volts:

28.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

15.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Coupling Position Quantity:

4

Mounting Facility Type And Quantity:

3 unthreaded hole

Mounting Facility Pattern:

Isosceles triangle single mounting facility pattern

Material:

Metal cover

Terminal Type And Quantity:

4 receptacle, coaxial and 3 solder stud

Specification Data:

12464-b80r0011 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0