

View Online at <https://aerobasegroup.com/nsn/5985-01-433-9725>

Body Style:

Rectangular

Overall Length:

2.780 inches

Overall Height:

Between 2.140 inches and 2.180 inches

Overall Width:

1.370 inches

Frequency Rating:

0.7 gigahertz single frequency voltage standing wave ratio and 1.3 gigahertz single frequency voltage standing wave ratio

Unthreaded Mounting Hole Diameter:

Between 0.144 inches and 0.154 inches

Switch Type:

Transfer

Longest Horizontal Distance Between Mounting Centers:

1.772 inches single mounting facility pattern and 1.788 inches single mounting facility pattern

Shortest Horizontal Distance Between Mounting Centers:

0.885 inches single mounting facility pattern and 0.895 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

1.082 inches single mounting facility pattern and 1.098 inches single mounting facility pattern

Shortest Vertical Distance Between Mounting Centers:

0.537 inches single mounting facility pattern and 0.553 inches single mounting facility pattern

Voltage Standing Wave Ratio:

1.15 single

Insertion Loss In Decibels:

0.15 single

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Minimum Crosstalk Rating In Decibels:

60.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

1.3 ac

Actuator Voltage In Volts:

28.0

Switch Operation Sequence:

Breaks before makes

Switch Return Mechanism Type:

Fail-safe

Coupling Position Quantity:

4

Mounting Facility Type And Quantity:

3 unthreaded hole

Mounting Facility Pattern:

Isosceles triangle single mounting facility pattern

Material:

Stainless steel body

Terminal Type And Quantity:

1 connector, receptacle and 4 receptacle, coaxial

Specification Data:

0vwl8-2134174 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0