

View Online at <https://aerobasegroup.com/nsn/5985-01-435-1920>

Body Style:

Rectangular

Frequency Rating:

2.0 gigahertz single frequency operating and 8.0 gigahertz single frequency operating

Unthreaded Mounting Hole Diameter:

Between 0.127 inches and 0.137 inches

Switch Type:

Nontransfer

Intermediate Horizontal Distance Between Mounting Centers:

1.250 inches single mounting facility pattern

Voltage Standing Wave Ratio:

1.70 single

Insertion Loss In Decibels:

2.50 single

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Minimum Crosstalk Rating In Decibels:

45.0 single

Actuator Operating Method:

Solid state

Switching Time:

200.0 nanoseconds

Pole Quantity:

1

Throw Quantity:

3

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position trapezoid single mounting facility pattern

Terminal Type And Quantity:

3 connector, receptacle and 5 pin

Specification Data:

31395-scd177302 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A158a0