NSN 5985-01-443-0263

Waveguide Assembly - Page 1 of 2



-443-0263

View Online at https://aerobasegroup.com/nsn/5985-01-
Cross Sectional Shape:
Internal, rectangular external, rectangular
Tubing Wall Construction Style:
Seamless all tubing segment
Tubing Twist Type:
Straight twist all tubing segment
Flange Quantity:
2
Voltage Standing Wave Ratio:
1.10
Insertion Loss In Decibels:
0.17
Maximum Operating Pressure:
30.0 pounds per square inch gage
Waveguide Outside Width:
1.000 inches
Waveguide Inside Width:
0.900 inches
Waveguide Inside Height:
0.400 inches
Waveguide Outside Height:
0.500 inches
Waveguide Longer Offset Distance:
14.550 inches
Flange Connecting Facility And Quantity:
4 unthreaded hole all flanges all connection facilities
Flange Style:
Cover type all flanges
Waveguide Offset Distance:
7.360 inches
Specified Frequency:
Between 8.2 gigahertz and 12.3 gigahertz
Special Features:
Exterior surfaces finished black oxide
Flexibility:
Rigid all tubing segment
Material:
Copper alloy single tubing segment
Style Designator:
Bend type
Shelf Life:

N/a

NSN 5985-01-443-0263

Waveguide Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0