NSN 5985-01-446-4101

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-446-4101

Application Design:
Transmission line
Body Style:
Rectangular terminal/terminals on three surfaces
Terminal Material:
Beryllium copper
Overall Length:
0.575 inches
Overall Height:
0.040 inches
Overall Width:
0.310 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
End Application:
B-1b
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
0.1 watts average
Rf Signal Attenuation In Decibels:
1.0
Attenuation Accuracy Reference Frequency:
0.0 hertz
Attenuation Accuracy In Decibels:
-0.10/+0.10
Temperature Sensitivity Attenuation In Decibels:
0.0001
Terminal Type And Quantity:
3 tab, solder lug
Frequency Range:
Between 0.000 hertz and 2.000 gigahertz
Special Features:
Attenuator, microwave, microstrip; maximum input power derated to 0 at 150 degrees c
Shelf Life:
N/a
Unit Of Measure:

NSN 5985-01-446-4101

Fixed Attenuator - Page 2 of 2

Demilitarization:

No

Fiig:

A20000

