## NSN 5985-01-449-4615

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-449-4615 **Application Design:** Transmission line **Body Style:** Rectangular terminal/terminals on three surfaces **Overall Length:** 0.147 inches **Overall Height:** 0.039 inches **Overall Width:** 0.123 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.30 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Power Rating:** 50.0 watts peak Rf Signal Attenuation In Decibels: 3.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+1.0 gigahertz **Attenuation Accuracy In Decibels:** -2.50/+3.50 **Frequency Sensitivity Attenuation In Decibels:** 1.00 **Terminal Type And Quantity:** 3 surface contact Frequency Range: Between 0.000 hertz and 1.000 gigahertz **Precious Material And Location:** Terminals gold and terminals platinum **Precious Material:** Gold and platinum Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

## **NSN 5985-01-449-4615** Fixed Attenuator - Page 2 of 2



Fiig:

A20000