

View Online at <https://aerobasegroup.com/nsn/5985-01-450-1346>

Body Style:

Rectangular

Overall Length:

2.460 inches

Overall Height:

2.160 inches

Overall Width:

1.320 inches

Frequency Rating:

8.0 gigahertz 3rd frequency operating and 12.4 gigahertz 3rd frequency operating

Unthreaded Mounting Hole Diameter:

0.149 inches

Switch Type:

Transfer

Longest Horizontal Distance Between Mounting Centers:

1.090 inches single mounting facility pattern

Shortest Horizontal Distance Between Mounting Centers:

0.545 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

1.780 inches single mounting facility pattern

End Application:

6625-01-324-1523

Voltage Standing Wave Ratio:

1.50 4th

Insertion Loss In Decibels:

0.70 5th

Minimum Crosstalk Rating In Decibels:

80.0 1st

Actuator Operating Method:

Solid state

Actuator Current Type And Rating In Amps:

0.350 dc

Actuator Voltage In Volts:

Between 20.0 and 26.0

Coupling Position Quantity:

4

Mounting Facility Type And Quantity:

3 unthreaded hole

Mounting Facility Pattern:

Isosceles triangle single mounting facility pattern

Special Features:

2p2t rf coaxial transfer switch

Material:

Aluminum body

Terminal Type And Quantity:

2 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0