NSN 5985-01-458-4482

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-458-4482

Application Design:
Transmission line
Body Material:
Aluminum alloy, qq-a-250/11, alloy 6061, t6
Body Style:
Rectangular, terminal/terminals on opposite surfaces
Overall Length:
Between 95.2 millimeters and 96.8 millimeters
Overall Height:
38.1 millimeters
Overall Width:
12.7 millimeters
Body Length:
Between 78.3 millimeters and 78.6 millimeters
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25 and 1.35 and 1.45
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
50.0 Coaxial Connector Series Designation:
Coaxial Connector Series Designation:
Coaxial Connector Series Designation: Sma
Coaxial Connector Series Designation: Sma Rf Signal Attenuation In Decibels:
Coaxial Connector Series Designation: Sma Rf Signal Attenuation In Decibels: 6.0
Coaxial Connector Series Designation: Sma Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range:
Coaxial Connector Series Designation: Sma Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +12.4/+18.0 gigahertz
Coaxial Connector Series Designation: Sma Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +12.4/+18.0 gigahertz Terminal Type And Quantity:
Coaxial Connector Series Designation: Sma Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +12.4/+18.0 gigahertz Terminal Type And Quantity: 2 connector
Coaxial Connector Series Designation: Sma Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +12.4/+18.0 gigahertz Terminal Type And Quantity: 2 connector Frequency Range:
Coaxial Connector Series Designation: Sma Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +12.4/+18.0 gigahertz Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz
Coaxial Connector Series Designation: Sma Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +12.4/+18.0 gigahertz Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Shelf Life:
Coaxial Connector Series Designation: Sma Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +12.4/+18.0 gigahertz Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Shelf Life: N/a
Coaxial Connector Series Designation: Sma Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +12.4/+18.0 gigahertz Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Shelf Life: N/a Unit Of Measure:
Coaxial Connector Series Designation: Sma Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +12.4/+18.0 gigahertz Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Shelf Life: N/a Unit Of Measure:
Coaxial Connector Series Designation: Sma Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+8.0 gigahertz and +12.4/+18.0 gigahertz Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Shelf Life: N/a Unit Of Measure: Demilitarization: