## NSN 5985-01-460-3262



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-460-3262 **Application Design:** Transmission line **Body Material:** Aluminum **Body Style:** Rectangular, terminal/terminals on opposite surfaces **Body Surface Treatment:** Paint, black **Overall Length:** 175.0 millimeters **Center To Center Distance Between Mounting Facilities Parallel To Width:** 57.2 millimeters **Overall Height:** 77.7 millimeters **Overall Width:** 77.7 millimeters **Mounting Hole/stud Quantity:** 4 and 4 Center To Center Distance Between Mounting Facilities Parallel To Height: 57.2 millimeters **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **End Application:** General purpose support and test equipment, anzac ships, weinschel corp Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Ν **Power Rating:** 150.0 watts average Rf Signal Attenuation In Decibels: 3.0 Mounting Facility Thread Size And Series/type Designator: 6.32-28 unc **Attenuation Accuracy In Decibels:** -0.01/+0.01 **Connection Type Per Function:** 

Female output and male input

**Mounting Method:** 

Threaded hole

## NSN 5985-01-460-3262

Fixed Attenuator - Page 2 of 2



## **Terminal Type And Quantity:**

2 connector

Frequency Range:

Between 0.000 hertz and 1.500 gigahertz

**Special Features:** 

Body length - 137.1 millimeters

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000