NSN 5985-01-463-6432

Radio Frequency Transmission Line Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-463-6432

Body Style:
Rectangular
Unthreaded Mounting Hole Diameter:
0.120 inches and 0.930 inches
Distance Between Mounting Facility Centers:
1.190 inches 2nd mounting facility pattern
Coaxial Connector Series Designation:
Sma
Connector End Design:
Female
Actuator Operating Method:
Solid state
Actuator Current Type And Rating In Amps:
0.120 dc
Actuator Voltage In Volts:
Between 24.0 and 30.0
Switching Time:
20.0 microseconds
Switch Return Mechanism Type:
Latching
Pole Quantity:
Pole Quantity:
•
1
1 Throw Quantity:
1 Throw Quantity: 2
1 Throw Quantity: 2 Mounting Facility Type And Quantity:
1 Throw Quantity: 2 Mounting Facility Type And Quantity: 4 unthreaded hole
1 Throw Quantity: 2 Mounting Facility Type And Quantity: 4 unthreaded hole Mounting Facility Pattern:
1 Throw Quantity: 2 Mounting Facility Type And Quantity: 4 unthreaded hole Mounting Facility Pattern: Two position in-line 1st mounting facility pattern
Throw Quantity: 2 Mounting Facility Type And Quantity: 4 unthreaded hole Mounting Facility Pattern: Two position in-line 1st mounting facility pattern Material:
Throw Quantity: 2 Mounting Facility Type And Quantity: 4 unthreaded hole Mounting Facility Pattern: Two position in-line 1st mounting facility pattern Material: Nickel body
Throw Quantity: 2 Mounting Facility Type And Quantity: 4 unthreaded hole Mounting Facility Pattern: Two position in-line 1st mounting facility pattern Material: Nickel body Terminal Type And Quantity:
Throw Quantity: 2 Mounting Facility Type And Quantity: 4 unthreaded hole Mounting Facility Pattern: Two position in-line 1st mounting facility pattern Material: Nickel body Terminal Type And Quantity: 3 tab, solder lug and 3 receptacle, coaxial
Throw Quantity: 2 Mounting Facility Type And Quantity: 4 unthreaded hole Mounting Facility Pattern: Two position in-line 1st mounting facility pattern Material: Nickel body Terminal Type And Quantity: 3 tab, solder lug and 3 receptacle, coaxial Shelf Life:
Throw Quantity: Mounting Facility Type And Quantity: 4 unthreaded hole Mounting Facility Pattern: Two position in-line 1st mounting facility pattern Material: Nickel body Terminal Type And Quantity: 3 tab, solder lug and 3 receptacle, coaxial Shelf Life: N/a
Throw Quantity: Mounting Facility Type And Quantity: 4 unthreaded hole Mounting Facility Pattern: Two position in-line 1st mounting facility pattern Material: Nickel body Terminal Type And Quantity: 3 tab, solder lug and 3 receptacle, coaxial Shelf Life: N/a
Throw Quantity: 2 Mounting Facility Type And Quantity: 4 unthreaded hole Mounting Facility Pattern: Two position in-line 1st mounting facility pattern Material: Nickel body Terminal Type And Quantity: 3 tab, solder lug and 3 receptacle, coaxial Shelf Life: N/a Unit Of Measure:
Throw Quantity: 2 Mounting Facility Type And Quantity: 4 unthreaded hole Mounting Facility Pattern: Two position in-line 1st mounting facility pattern Material: Nickel body Terminal Type And Quantity: 3 tab, solder lug and 3 receptacle, coaxial Shelf Life: N/a Unit Of Measure: Demilitarization: