NSN 5985-01-463-7623

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-463-7623

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange all connection facilities

Thread Direction:

Right-hand second flange all connection facilities

End Application:

Apg180 txmite, next assembly g1-28-5640

Flange Quantity:

2

Flange Inside Width:

0.900 inches second flange

Flange Inside Height:

0.400 inches second flange

Flange Outside Width:

1.630 inches second flange

Flange Outside Height:

1.630 inches second flange

Flange Depth:

0.437 inches second flange

Flange Connecting Hole Diameter:

0.169 inches first flange all connection facilities and 0.172 inches first flange all connection facilities

Voltage Standing Wave Ratio:

1.05

Thready Qty Per Inch (tpi):

32 second flange all connection facilities

Thread Size:

0.164 inches second flange all connection facilities

Waveguide Inside Width:

0.900 inches

Waveguide Inside Height:

0.400 inches

Waveguide Longer Offset Distance:

1.680 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Offset Distance:

1.680 inches

Specified Frequency:

Between 8.2 gigahertz and 12.4 gigahertz

NSN 5985-01-463-7623 Waveguide Assembly - Page 2 of 2



| Special Features: |
|--|
| 90 deg. H-plane |
| Flexibility: |
| Rigid single tubing segment |
| Material: |
| Copper alloy all tubing segment and flange or zinc alloy all tubing segment and flange |
| Style Designator: |
| Bend type |
| Thread Series Designator: |
| Unc second flange all connection facilities |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A073a0 |