

NSN 5985-01-467-2881 Fixed Attenuator - Page 1 of 2	AeroBas Grou
View Online at https://aerobasegroup.com/nsn/5985-01-467-2881	
Application Design:	
Transmission line	
Body Material:	
Brass, qq-b-626, comp 22, 1/2h	
Body Style:	
Err-090	
Body Surface Treatment:	
Silver plated, qq-s-365	
Overall Length:	
2.688 inches	
Overall Diameter:	
0.812 inches	
Operating Tempurature Range:	

-55.0/+125.0 degrees celsius

Voltage Standing Wave Ratio:

1.20 and 1.25

Input Impedance Rating In Ohms:

Output Impedance Rating In Ohms:

50.0

50.0

Coaxial Connector Series Designation:

Ν

Power Rating:

2.0 watts average and 300.0 watts peak

Rf Signal Attenuation In Decibels:

40.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+3.0 gigahertz and +3.0/+6.0 gigahertz

Attenuation Accuracy Reference Frequency:

6.0 gigahertz

Attenuation Accuracy In Decibels:

-1.00/+1.00

Connection Type Per Function:

Female output and male input

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 6.000 gigahertz

Precious Material And Location:

Body surfaces silver

NSN 5985-01-467-2881

Fixed Attenuator - Page 2 of 2



	P	reci	ious	Μ	ate	∍ria	al:
--	---	------	------	---	-----	------	-----

Silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000