NSN 5985-01-468-6482

Electrical Dummy Load - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-468-6482

Ambient Tempurature In Deg Celsius At Full Rated Power:
-40.0 and 40.0
Overall Length: 6.740 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.600 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.750 inches
Overall Height:
10.400 inches
Overall Width:
2.800 inches
Impedance Rating In Ohms:
50.0
Body Length:
6.000 inches
Body Height:
10.000 inches
Frequency Range Rating:
+1.000/+2.400 gigahertz
Voltage Standing Wave Ratio:
1.10
1.10 Power Rating:
Power Rating:
Power Rating: 150.000 watts average
Power Rating: 150.000 watts average Voltage Standing Wave Ratio Frequency Range:
Power Rating: 150.000 watts average Voltage Standing Wave Ratio Frequency Range: +1.000/+2.400 gigahertz
Power Rating: 150.000 watts average Voltage Standing Wave Ratio Frequency Range: +1.000/+2.400 gigahertz Termination Type:
Power Rating: 150.000 watts average Voltage Standing Wave Ratio Frequency Range: +1.000/+2.400 gigahertz Termination Type: Connector receptacle
Power Rating: 150.000 watts average Voltage Standing Wave Ratio Frequency Range: +1.000/+2.400 gigahertz Termination Type: Connector receptacle Operating Position:
Power Rating: 150.000 watts average Voltage Standing Wave Ratio Frequency Range: +1.000/+2.400 gigahertz Termination Type: Connector receptacle Operating Position: Vertical
Power Rating: 150.000 watts average Voltage Standing Wave Ratio Frequency Range: +1.000/+2.400 gigahertz Termination Type: Connector receptacle Operating Position: Vertical Cooling Method:
Power Rating: 150.000 watts average Voltage Standing Wave Ratio Frequency Range: +1.000/+2.400 gigahertz Termination Type: Connector receptacle Operating Position: Vertical Cooling Method: Self-cooled
Power Rating: 150.000 watts average Voltage Standing Wave Ratio Frequency Range: +1.000/+2.400 gigahertz Termination Type: Connector receptacle Operating Position: Vertical Cooling Method: Self-cooled Style Designator:
Power Rating: 150.000 watts average Voltage Standing Wave Ratio Frequency Range: +1.000/+2.400 gigahertz Termination Type: Connector receptacle Operating Position: Vertical Cooling Method: Self-cooled Style Designator: Rf connector, 4 hole mounted
Power Rating: 150.000 watts average Voltage Standing Wave Ratio Frequency Range: +1.000/+2.400 gigahertz Termination Type: Connector receptacle Operating Position: Vertical Cooling Method: Self-cooled Style Designator: Rf connector, 4 hole mounted Shelf Life:
Power Rating: 150.000 watts average Voltage Standing Wave Ratio Frequency Range: +1.000/+2.400 gigahertz Termination Type: Connector receptacle Operating Position: Vertical Cooling Method: Self-cooled Style Designator: Rf connector, 4 hole mounted Shelf Life: N/a
Power Rating: 150.000 watts average Voltage Standing Wave Ratio Frequency Range: +1.000/+2.400 gigahertz Termination Type: Connector receptacle Operating Position: Vertical Cooling Method: Self-cooled Style Designator: Rf connector, 4 hole mounted Shelf Life: N/a
Power Rating: 150.000 watts average Voltage Standing Wave Ratio Frequency Range: +1.000/+2.400 gigahertz Termination Type: Connector receptacle Operating Position: Vertical Cooling Method: Self-cooled Style Designator: Rf connector, 4 hole mounted Shelf Life: N/a Unit Of Measure:

A19800