# NSN 5985-01-470-5792

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-470-5792

Application	Design:
	- • • ·

Transmission line

**Body Material:** 

Aluminum

Body Style:

Coaxial type

## **Overall Length:**

3.000 inches

#### **Overall Height:**

0.900 inches

**Overall Width:** 

0.870 inches

**Operating Tempurature Range:** 

-55.0/+71.0 degrees celsius

#### **End Application:**

Sea dart depot automatic test equipment

### Voltage Standing Wave Ratio:

1.25 and 1.35

**Power Rating:** 

1.0 watts average and 100.0 watts peak

## **Overall Attenuation Range In Decibels:**

+0.5/+127.0

#### **Attenuation Variation Method:**

Stepped

#### **Step Position Quantity:**

5

#### Attenuation Per Step In Decibels:

1.0 and 0.25 and 10.0 and 0.50

#### **Frequency Range:**

Between 0.000 hertz and 2.000 gigahertz

### Adjustment Device Type And Quantity:

1 electronic, programmable

#### Impedance Rating In Ohms:

50.0 input-output

## **Terminal Type And Quantity:**

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

# NSN 5985-01-470-5792

Variable Attenuator - Page 2 of 2

**Fiig:** A223a0

