

View Online at <https://aerobasegroup.com/nsn/5985-01-473-1026>

Thread Class:

2b mounting facility hole

Body Style:

Cylindrical

Overall Length:

2.930 inches

Overall Height:

3.200 inches

Overall Width:

3.000 inches

Frequency Rating:

3.0 gigahertz single frequency operating

Switch Type:

Nontransfer

Operating Temperature Range:

-35.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.20 single

Insertion Loss In Decibels:

0.20 single

Coaxial Connector Series Designation:

Tnc

Connector End Design:

Female

Rf Power Handling Capability:

300.0 watts average single

Minimum Crosstalk Rating In Decibels:

80.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.16 dc

Actuator Voltage In Volts:

Between 24.0 and 30.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

15.0 milliseconds

Pole Quantity:

1

Throw Quantity:

7

Coupling Position Quantity:

8

Mounting Facility Type And Quantity:

4 threaded hole

Thready Qty Per Inch (tpi):

32 mounting facility hole

Thread Size:

0.164 inches mounting facility hole

Mounting Facility Pattern:

Four position circular single mounting facility pattern

Material:

Beryllium contact (s) and copper contact(s)

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Surface Treatment:

Nickel connecto (s) all surfaces

Surface Treatment Specification:

Mil-g-45204 military specification single treatment response contact (s) all surfaces

Thread Series Designator:

Unc mounting facility hole

Terminal Type And Quantity:

9 turret and 8 plug, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0

Mil-std (military Standard):

Mil-c-26074 spec.