NSN 5985-01-473-9984

Waveguide Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-473-9984

Thread Class: 2b mounting facility hole **Body Style:** Rectangular **Overall Length:** 5.900 inches **Overall Height:** 2.200 inches **Overall Width:** 2.200 inches Frequency Rating: 9.0 gigahertz single frequency operating and 10.0 gigahertz single frequency operating Switch Type: Transfer **Voltage Standing Wave Ratio:** 1.10 single **Insertion Loss In Decibels:** 0.10 single Minimum Crosstalk Rating In Decibels: 80.0 single **Actuator Operating Method:** Relay **Actuator Current Type And Rating In Amps:** 0.50 ac **Actuator Voltage In Volts:** 115.0 **Switch Operation Sequence:** Makes before breaks **Switching Time:** 100.0 milliseconds Switch Return Mechanism Type: Fail-safe **Waveguide Flange Type:** Cover **Coupling Position Quantity: Mounting Facility Type And Quantity:** 4 threaded hole

Thread Size:

0.250 inches mounting facility hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

NSN 5985-01-473-9984

Waveguide Switch - Page 2 of 2



Elango	Connecting	- Eacility	, And	Quantity	,.
rianue	Connecting	ı racılıtı	/ Ana	Quantity	/ E

1 quick disconnect fasteners

Special Features:

R-f power 20 kw peak, 600 w avg.

Material:

Aluminum body

Surface Treatment:

Enamel body all surfaces

Thread Series Designator:

Unc mounting facility hole

Terminal Type And Quantity:

4 wire lead

Shelf Life:

Unit Of Measure:

N/a

Demilitarization:

Yes - demil/mli

Fiig:

A158a0