NSN 5985-01-474-2143

Waveguide Adapter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-474-2143

Cross Sectional Shape:
Internal, rectangular external, rectangular
Tubing Wall Construction Style:
Seamless all tubing segment
Flange Quantity:
2
Flange Inside Width:
1.255 inches all flanges
Flange Inside Height:
0.630 inches all flanges
Flange Outside Width:
1.875 inches all flanges
Flange Outside Height:
1.875 inches all flanges
Flange Depth:
0.438 inches all flanges
Flange Connecting Hole Diameter:
0.169 inches all flanges all connection facilities
Coaxial Connector Series Designation:
Sma
Connector End Design:
Connector End Design: Female
-
Female
Female Flange Connecting Facility And Quantity:
Female Flange Connecting Facility And Quantity: 4 unthreaded hole all flanges all connection facilities
Female Flange Connecting Facility And Quantity: 4 unthreaded hole all flanges all connection facilities Flange Style:
Female Flange Connecting Facility And Quantity: 4 unthreaded hole all flanges all connection facilities Flange Style: Choke type all flanges
Female Flange Connecting Facility And Quantity: 4 unthreaded hole all flanges all connection facilities Flange Style: Choke type all flanges Special Features:
Female Flange Connecting Facility And Quantity: 4 unthreaded hole all flanges all connection facilities Flange Style: Choke type all flanges Special Features: Frequency: 7.9 to 8.4 ghz; coupling: 40 decibels (both ports), directivity: 20 decibels (both ports)
Female Flange Connecting Facility And Quantity: 4 unthreaded hole all flanges all connection facilities Flange Style: Choke type all flanges Special Features: Frequency: 7.9 to 8.4 ghz; coupling: 40 decibels (both ports), directivity: 20 decibels (both ports) Material:
Female Flange Connecting Facility And Quantity: 4 unthreaded hole all flanges all connection facilities Flange Style: Choke type all flanges Special Features: Frequency: 7.9 to 8.4 ghz; coupling: 40 decibels (both ports), directivity: 20 decibels (both ports) Material: Aluminum all tubing segment and flange
Female Flange Connecting Facility And Quantity: 4 unthreaded hole all flanges all connection facilities Flange Style: Choke type all flanges Special Features: Frequency: 7.9 to 8.4 ghz; coupling: 40 decibels (both ports), directivity: 20 decibels (both ports) Material: Aluminum all tubing segment and flange Shelf Life:
Female Flange Connecting Facility And Quantity: 4 unthreaded hole all flanges all connection facilities Flange Style: Choke type all flanges Special Features: Frequency: 7.9 to 8.4 ghz; coupling: 40 decibels (both ports), directivity: 20 decibels (both ports) Material: Aluminum all tubing segment and flange Shelf Life: N/a Unit Of Measure:
Flange Connecting Facility And Quantity: 4 unthreaded hole all flanges all connection facilities Flange Style: Choke type all flanges Special Features: Frequency: 7.9 to 8.4 ghz; coupling: 40 decibels (both ports), directivity: 20 decibels (both ports) Material: Aluminum all tubing segment and flange Shelf Life: N/a
Female Flange Connecting Facility And Quantity: 4 unthreaded hole all flanges all connection facilities Flange Style: Choke type all flanges Special Features: Frequency: 7.9 to 8.4 ghz; coupling: 40 decibels (both ports), directivity: 20 decibels (both ports) Material: Aluminum all tubing segment and flange Shelf Life: N/a Unit Of Measure:

A073a0