

View Online at <https://aerobasegroup.com/nsn/5985-01-477-2194>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches all flanges and 1.006 inches all flanges

Flange Inside Height:

0.503 inches all flanges and 0.503 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities and 0.172 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.25

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

Waveguide Height:

4.775 inches

Flexibility:

Flexible single tubing segment

Material:

Rubber natural single tubing jacket

Precious Material And Location:

External and internal surfaces of tubing and flanges silver and external and internal surfaces of tubing and flanges rhodium

Precious Material:

Silver and rhodium

Surface Treatment:

Silver all tubing segment and flange all surfaces and rhodium all tubing segment and flange all surfaces

Style Designator:

U-bend type

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0