NSN 5985-01-478-2446

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-478-2446

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
56.1 millimeters
Overall Height:
40.0 millimeters
Overall Width:
30.0 millimeters
End Application:
Gps tsts, wsd: global positioning system an/fsq-141
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average and 100.0 watts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.7
Overall Attenuation Range In Decibels:
+0.0/+70.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
70
Attenuation Per Step In Decibels:
1.0
Frequency Range:
Between 0.000 gigahertz and 2.500 gigahertz
Adjustment Device Type And Quantity:
1 knob
Impedance Rating In Ohms:
50.0 input-output
Special Features:
Switching life: 1, 000, 000 steps
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
NI .

No

NSN 5985-01-478-2446

Variable Attenuator - Page 2 of 2



Fiig:

A223a0